

XS-NVR2104-4KH

X-Security NVR for IP cameras

4 CH IP video

Maximum recording resolution 8 Mpx

Compression H.265 / H.264

Outputs 4K HDMI & VGA

Supports 1 hard disk



X-Security

NVR for IP cameras

4 CH

80 Mbps bandwidth supported

Maximum resolution 8 Megapixel (in 1 channel)

Compression H.265 / H.264

VGA and HDMI 4K output

IP Dual Stream Access

Mouse

Space for 1 HDD

WEB, CMS (DSS/PSS), Smartphone and NVR interface

ONVIF Compatible

Specifications

Brand	X-SECURITY
Inputs for IP cameras	LAN port up to 4 channels
PoE	Does not have
IP compatible cameras	X-SECURITY (proprietary protocol), HIKVISION, SAFIRE, ONVIF
Video outputs	1 HDMI 4K, 1 VGA
Bidirectional audio	1 input, 1 output, RCA
Video compression format	H.265 / H.264
Display resolution	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768
Total bandwidth	80 Mbps
Recording resolution	8Mp (1 channel), 6Mp, 5Mp, 4Mp, 3Mp, 1080P, 720P, D1 ...
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Alarms	Does not have
Recording method	Manual, programmed, motion detection
Backup	USB (Memory, HDD, CD-RW, DVR-RW) / Network / SATA internal interface
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2x USB 2.0 (Mouse and backup) /1 RJ45 10/100M (Ethernet)
Remote access	Browser (ActiveX), mobile app or softwarePSS
Power	DC 12 V / 2.0 A
Dimensions	48 (H) x 225 (W) x 260 (D) mm / 1.6 Kg (without HDD)