

XS-IPB830ZSWH-4P

4Mpx IP PRO Camera

1/3" Progressive CMOS

Compression H.265+ / H.265 /

H.264+ / H.264

2.7~13.5 mm Motorised Varifocal

Lens

WDR | IR LEDs range 60 m

Weatherproof IP67



X-Security

IP camera

Pro range

1/3" Progressive CMOS

4 Megapixel (2688x1520)

2.7~13.5 mm motorised varifocal autofocus lens

High sensitivity Starlight

0.008 Lux

IR Array Range 60 m

Compression H.265+/H.265/H.264+/H.264

RJ-45 10/100 BaseT

PoE IEEE802.3af

Weatherproof IP67

WDR

IR Cut

SD card recording

Intelligent detection: line crossing, intrusion

WEB Interface, CMS (DSS/ PSS), Smartphone and NVR

ONVIF Compatible

Specifications

Brand	X-Security
Image sensor	1/3" Progressive CMOS
Maximum resolution	4 Megapixel (2688x1520)
Main Stream rate	4Mpx (1 ~ 20fps)/3Mpx(1 ~ 25/30fps)
Extra Stream rate	D1/CIF(1 ~ 25/30fps)
Compression	H.265+/H.265/H.264+/H.264
Bitrate	H.265: 12K ~ 6400Kbps H.264: 32K ~ 10240Kbps
Lens	2.7mm~13.5mm motorized HF
Minimum illumination	0.008Lux/F1.4(Color,1/3s,30IRE)
Infrared lighting	0 Lux / IR LEDs Array (60 m)
Image improvements	WDR, Smart IR, BLC, HLC, AWB, AGC, 3D-NR, Privacy Masking, Motion Detection, ROI
Video analysis	Line crossing Area intrusion
Day / Night	Removable mechanical ICR filter
Network interface	Ethernet 10/100 BaseT
Internal memory	Slot for MicroSD card, Max 128 GB
Remote access	Web browser, CMS Software (DSS/PSS), Smartphone (DMSS) and NVR
Interoperability	ONVIF
Power	DC 12 V / 1000 mA, PoE IEEE802.3af
Degree of protection	Weatherproof IP67
Temp. operation	-30° C ~ +60° C
Dimensions	244 mm (Fo) x 79 (An) x 76 (Al) mm
Weight	0.815 Kg