XS-AC1201-MFP

Access and Attendance control
MF Card and keyboard
30.000 recordings / 150.000 records
TCP/IP, USB, RS485, Wiegand &
Relay
Valid for interior
Compatible with SmartPSS software



X-Security

Stand-alone reader of access and time & attendance Identification by MF card, password and/or combinations Touch keypad

Capacity or up to 30.000 users & 150.000 registers
128 groups, schedules and holiday calendars
Communication TCP/IP, RS485, miniUSB and Wiegand 26
Integrated controller (door sensor, push button, bell and relay)
Alarm input and output
Control of schedules, shifts and cycles
Anti-Passback and Lock Function

Complete SmartPSS management software included

Specifications

Brand	X-Security
Hardware CPU	32 Bit Processor + 16MB RAM
Read time	< 0.1 Sec.
Capacity	Up to 30.000 EM RFID cards
Records	150.000 registers
Identification modes	Card, PIN & combinations
Proximity card	MF (13.56 MHz)
Screen	No
Communication	TCP/IP, USB
Outputs	Wiegand OUT, RS485, Relay, Alarm, Doorbell
Inputs	Door sensor, Open button, Alarm
Special functions	Anti-passback, multi-card open
Software	SmartPSS
Power	DC 9~15 V / 200 mA max.
Degree of protection	IP67
Temp. operation	-5° C ~ +55° C
Dimensions	97 (W) x 150 (H) x 16 (D) mm
Weight	300 g