

OC-HUMO-F4N1

1080p PRO Series hidden camera
4 in 1 (HDTVI / HDCVI / AHD / CVBS)
1/2.9" Sony© 2.12 Mpx Exmor
IMX322
3.6 mm Pinhole Lens
Minimum illumination 0.1 Lux
OSD Menu



Camera disguised as a smoke alarm. Technology 4 in 1 (HDTVI / HDCVI / AHD / CVBS) Range 1080p PRO.

Consisting of a 1/2.9" Sony© 2.12 Megapixel Exmor sensor (model IMX322) and DSP (model V30), which offers a resolution of 1080p at 25 FPS. 3.6mm fixed Pinhole lens with a diagonal FOV of 79°. Minimum illumination of 0.1 Lux.

OSD Menu in HD format, remotely accessible from the recorder via the coaxial cable connection or via the integrated multi-function button, for configuring the cameras parameters:

ATR, Adaptive Tone Reproduction which improves the gradient and the definition
AE Shutter, automatic exposure control to optimize the input of received light
2D-NR, digital noise reduction system without loss of focus
AWB, automatic white balance for true colours

BNC video connection in high definition formats HDTVI / HDCVI / AHD / CVBS, switchable with button.

PVC housing, for interior use. Easy ceiling mount.

Specifications

| | |
|----------------------------|---|
| Range | 1080p PRO |
| Image sensor | 1/2.9" Sony© 2.12 Megapixel Exmor (model IMX322) |
| DSP | V30 |
| Resolution | HD 1080p (1920x1080) at 25 FPS / CVBS 1000TVL |
| Video output | 1 x BNC switchable HDTVl 2.0 / HDCVI / AHD / CVBS |
| Minimum illumination | 0.1 Lux |
| Basic functions | OSD menu (remote), Day/Night with IR-CUT (ICR), ATR |
| Configurable OSD functions | DWDR, 2D-NR, AE, AWB, AGC |
| Lens | 3.6 mm (79°) |
| Power | DC 12 V / 300 mA |
| Degree of protection | Interior |
| Temp. operation | -10° C ~ +50° C |
| Dimensions | 57 (H) x 120 (Ø) mm |
| Weight | 70 g |