

XS-XVR6216S-4KL

DVR 5n1 X-Security

16 CH HDTVII/HDCVI/AHD/CVBS

(4K) + 8 IP (4K)

2 SATA Ports Up to 8TB

Audio over coaxial



X-Security

DVR 5n1

16 CH video HDTVII/HDCVI/AHD/CVBS / 16+8 IP / 16 CH audio

H.264+/H.264

Resolution 4K(7FPS); 5MP(12FPS); 4MP/3MP(15FPS); 1080P/720P/960H/D1/CIF/QCIF (25FPS) [%VAR%]

PTZ Control (RS485/Coaxial)

Audio over coaxial

HDMI Full HD, VGA & CVBS Outputs

Mouse

2 USB Ports

Space for 2 HDD

Compact size

Specifications

Brand	X-Security
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	16 Channels BNC (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 24 IP Channels (6Mpx), replacing all the BNC channels
Video outputs	1 HDMI 4K, 1 VGA
Video / audio compression	H.264+/H.264
Display resolution	HDMI: 4K, 2560×1440, 1920×1080, 1280×1024, 1280×720, 1024×768 VGA: 1920×1080, 1280×1024, 1280×720, 1024×768
Total bandwidth	128 Mbps
Recording resolution	4K(7FPS); 5MP(12FPS); 4MP/3MP(15FPS); 1080P/720P/960H/D1/CIF/QCIF (25FPS)
Main Coding	All channel: 4K(7FPS); 5MP(12FPS); 4MP/3MP(15FPS); 1080P/720P/960H/D1/CIF/QCIF (25FPS)
Dual-Stream encoding	960H(1~15fps)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Audio inputs	16 BNC, 1 RCA Channel
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Alarms	No
Video analysis	IVS: Tripwire Area intrusion Abandoned object Face detection
Face detection	Up to 1 analog live face detection channel
Recording method	Manual, programmed, motion detection, alarm
Backup	USB / Network
Internal memory	2 SATA HDD 3.5" of up to 16 TB (not included)
Communication	RS485 (PTZ) /2 x USB (Mouse and backup) / RJ45 10/100 (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12V / 2A
Dimensions / Weight	47.6 (H) x 260 (W) x 237.4 (D) mm / 1.17 Kg